

# LUBRICANTS FOR FIAT CHRYSLER AUTOMOBILES PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Fiat Chrysler Automobiles.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN GT1 FLEX 5 SAE 0W-20</b>  <b>BluEV</b> TECHNOLOGY	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO2 emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. Additionally applicable in hybrid vehicles of different manufacturers such as Toyota or Mercedes-Benz.	ACEA C6, C5 API SN PLUS RC API SP RC	MB-APPROVAL 229.71 MB-APPROVAL 229.72	CHRYSLER MS- 12145 FIAT 9.55535-GSX
<b>TITAN GT1 PRO FPW03 SAE 5W-30</b>	Premium Performance engine oil for passenger cars and light commercial vehicles, specially developed for Stellantis engines requiring the new specification FPW9.55535/03. Optimum cold starting, reduced oil consumption, and minimised exhaust emissions.	ACEA C3 API SQ	–	OPEL OV0401547 – D30 OPEL OV0401547 – G30 PSA B71 2290 PSA B71 2297 STELLANTIS FPW9.55535/03
<b>TITAN GT1 FLEX C23 SAE 5W-30</b>  <b>BluEV</b> TECHNOLOGY	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C3, C2 API SQ	MB-APPROVAL 229.51 MB-APPROVAL 229.52	CHRYSLER MS- 11106 FIAT 9.55535-S1 / - S3 IVECO 18-1811 CLASSE SC1 MB 229.31
<b>TITAN GT1 FLEX 3 SAE 5W-40</b>	Premium Performance engine oil. Optimum cold starting, reduced oil consumption, and minimised exhaust emissions. For modern passenger cars and light commercial vehicles with or without extended oil drain intervals. Especially developed for vehicles with exhaust aftertreatment and turbocharger.	ACEA C3 API SN	MB- APPROVAL 226.5 MB- APPROVAL 229.31 MB- APPROVAL 229.51 MB- APPROVAL 229.52	API CF CHRYSLER MS- 10725 FIAT 9.55535-GH2 FIAT 9.55535-S2 FIAT 9.55535-T2
<b>TITAN SUPERSYN F ECO-DT SAE 5W-30</b>	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A5/B5 API SL	–	ACEA A1/B1 API CF CHRYSLER MS 6395 IVECO 18-1811 CLASSE S1/S2
<b>TITAN SUPERSYN D1 SAE 0W-20</b>	Ultra High Performance, extreme fuel economy engine oil, specially developed for GM gasoline engines requiring dexos1™ Gen 2 fluid. Optimum cold starting, lower oil consumption and minimised exhaust emissions.	API SN PLUS RC API SP RC ILSAC GF-6A	–	CHRYSLER MS-6395 CHRYSLER MS-12145 FIAT 9.55535-CR1 FIAT 9.55535-GSX ILSAC GF-5
<b>TITAN SUPERSYN D1 SAE 5W-30</b>	Ultra High Performance, extreme fuel economy engine oil, specially developed for gasoline engines requiring dexos1™ Gen 2 fluid. Optimum cold starting, lower oil consumption and minimised exhaust emissions.	API SN PLUS RC API SP RC ILSAC GF-6A	–	CHRYSLER MS-6395 FIAT 9.55535-CR1 ILSAC GF-5

## Automatic Transmission Fluids (ATF)

# LUBRICANTS FOR FIAT CHRYSLER AUTOMOBILES PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN ATF 6400</b>   Advanced Circular Technologies	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.	JASO M315 TYPE 1A-LV	DEXRON VI ZF TE-ML 09	AISIN WARNER/ AW-1 FIAT 9.55550-AV2 FIAT 9.55550-AV6 JWS 3324
<b>TITAN ATF 6008</b>   Advanced Circular Technologies	Premium Performance ATF, specially developed to optimize the shifting performance of ZF automatic transmissions incl. hybrid applications. Product dyeing: green.	–	–	CHRYSLER 68157995AA FIAT 9.55550-AV5
<b>TITAN ATF 4400</b>   Advanced Circular Technologies	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III (H) CHRYSLER MS7176E/9602 (ATF +3/+4) FIAT 9.55550-AV1/AV4 JWS 3309/TYPET-IV
<b>Continuously Variable Transmission Fluids (CVTF)</b>				
<b>TITAN CVTF FLEX</b>   Advanced Circular Technologies	Premium Performance CVTF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	CHRYSLER CVTF+4 DODGE/JEEP NS-2/CVTF+4
<b>Gear Oils</b>				
<b>TITAN SINTOFLUID FE SAE 75W</b>   TECHNOLOGY	Premium Performance Manual Transmission Fluid offering increased efficiency in passenger cars due to its low viscosity and can also be used in reducer gearboxes of hybrid vehicles. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
<b>TITAN SINTOFLUID SAE 75W-80</b>	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
<b>TITAN SINTOPOID LS SAE 75W-90</b>	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 inkl. LS	–	–
<b>TITAN SINTOPOID LS SAE 75W-140</b>	Premium Performance Gear Oil for axle and transfer gearboxes, formulated with fully-synthetic base oils. Suitable for axle and transfer gearboxes with and without limited slip differential.	API GL-5	–	CHRYSLER MS-8985

## Antifreeze

# LUBRICANTS FOR FIAT CHRYSLER AUTOMOBILES PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>FRICOFIN PS</b>  	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites and borates with PSi-OAT-technology. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: green.	ASTM D3306-20 TYPE I ASTM D4985 BS 6580.2010	–	Chrysler MS 7170 FIAT 9.55523
<b>Brake Fluids</b>				
<b>TITAN DOT 514 LV</b>  	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	–
<b>Greases</b>				
<b>Renolit LX-PEP 2</b>	Multipurpose grease, wheel bearings of motor vehicles, roller bearings of e-motors, needle bearings of cardan shafts, plain and roller bearings, ventilator grease.	KP 2 N-30 ISO-L-XC(F)DEB 2	MB Freigabe 265.1, ZF TE-ML 12, Schaeffler Gruppe, VW TL 52 147 X, Interprecise (IDC-Bearings), Deutsche Bahn	–
<b>Renolit JP 1619</b>	EP-grease with additive for improve corrosion protection, ageing resistance and adhesiveness, lubrication of friction points requiring very good sliding behaviour, low start-up resistance, also at low temperature, e.g. rack and pinion steerings, prop shafts, high-speed bearings	–	Dana Spicer Bosch	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 01/2026

FUCHS LUBRICANTS GERMANY GmbH  
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

