

# LUBRICANTS FOR RENAULT COMMERCIAL VEHICLES




Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Renault.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN CARGO MAXX II SAE 5W-30</b>	Premium MAXX Performance Engine Oil. Especially developed for vehicles with exhaust aftertreatment and turbocharger. Optimum cold start properties and ageing stability for a very good fuel economy throughout the drain interval.	ACEA E11, E8, E7, E4 API CK-4/CJ-4 CAT ECF-3 JASO DH-1/DH-2/DL-0	RENAULT RLD-3	RENAULT RLD-4
<b>TITAN CARGO MAXX II SAE 10W-40</b>	Premium MAXX Performance Engine Oil. Especially developed for vehicles with exhaust aftertreatment and turbocharger. Good cold start properties and excellent ageing stability for fuel economy throughout the drain interval.	ACEA E11, E8, E7, E4 API CK-4/CJ-4 CAT ECF-3 JASO DH-1/DL-0 JASO DH-2	RENAULT RLD-3	RENAULT RLD-4
<b>TITAN CARGO FLEX A-4 SAE 5W-30</b>	Premium Performance, extreme fuel-economy engine oil. Specially developed for commercial vehicles with modern exhaust after treatment systems. Suitable for Euro VI engines. Offers good cold starting and lower oil consumption.	API FA-4	RENAULT RLD-5	–
<b>TITAN CARGO SAE 5W-40</b>	Premium Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger.	ACEA E11 API CK-4/CJ-4/SN CAT ECF-3	RENAULT RLD-3	RENAULT RLD-4
<b>TITAN CARGO SAE 15W-40</b>	Premium Performance, fuel-economy engine oil for a variety of commercial vehicle diesel engines. Specially developed for vehicles with extended service intervals, exhaust after treatment and turbocharger.	ACEA E11, E7 API CK-4/CJ-4/SN CAT ECF-3 JASO DH-2	RENAULT RLD-3	RENAULT RLD-4
<b>Gear Oils</b>				
<b>TITAN CYTRAC TD SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed manual transmissions and hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals.	API GL-4/GL-5 API MT-1 SAE J2360	VOLVO 97312	–
<b>TITAN CYTRAC SL SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals in commercial vehicle axle drives.	API GL-5	–	VOLVO 97312 ZF TE-ML 05B, 07, 08, 12B, 16F, 17B
<b>TITAN CYTRAC ULTRA SYNTH SAE 75W-80</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals.	API GL-4 VOLVO 97307	ZF TE-ML 01E, 02E, 16P (ZF008388)	–
<b>TITAN CYTRAC MAT SAE 75W-80</b>	Premium Performance Gear Oil for gear boxes in commercial vehicles, specially developed for manual and automatic ZF-gear boxes, formulated with selected base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals and compatible with Carbon-Synchronizers.	API GL-4	–	VOLVO 97305 VOLVO 97307 ZF TE-ML 01E, 02D, 02E, 08, 16P
<b>TITAN SUPERGEAR MC SAE 80W-90</b>	Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	–	VOLVO 97310

# LUBRICANTS FOR RENAULT COMMERCIAL VEHICLES



Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN SUPERGEAR MC SAE 80W-140</b>	Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	–	ZF TE-ML 05A, 12M, 16C, 21A (ZF006028)	RENAULT VI
<b>Automatikgetriebeöle (ATF)</b>				
<b>TITAN ATF 5500</b>	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: none.	–	VOLVO 97341	ALLISON TES 389 ALLISON TES 289
<b>TITAN ATF 4000</b>	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	VOLVO 97341	ALLISON TES 389
<b>Antifreeze</b>				
<b>FRICOFIN LD</b>	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF	–	AS/NZS 2108.1-1997
<b>Brake Fluids</b>				
<b>TITAN DOT 514 LV</b> 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	RENAULT 41-02-001/--H
<b>Greases</b>				
<b>RENOLIT FLM 2</b>	For mechanically loaded lubricating points, grease with MoS <sub>2</sub> , agricultural machines, commercial vehicles, construction industry, quarries and mining, rubber and concrete factory	KPF 2 N-30 ISO-L- XC(F)DEB 2	–	–
<b>RENOLIT LZR 000</b>	Semi-fluid grease for central lubricating systems of commercial vehicles	GP 00-000 G-40	–	–
<b>RENOLIT LX-PEP 2</b>	Multipurpose grease, wheel bearings of motor vehicles, roller bearings of e-motors, needle bearings of cardan shafts, plain and roller bearings, ventilator grease.	KP 2 N-30 ISO-L- XC(F)DEB 2	–	–
<b>RENOLIT MP 735</b>	Multipurpose grease, roller and plain bearings in the chassis area.	KP 2 K-40 ISO-L- XD(F)CEB 2	–	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 01/2026

# LUBRICANTS FOR RENAULT COMMERCIAL VEHICLES



---

Product name	Description	Specifications	Approvals	FUCHS Recommendations
--------------	-------------	----------------	-----------	-----------------------

---

FUCHS LUBRICANTS GERMANY GmbH  
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
E-Mail: [export-flg@fuchs.com](mailto:export-flg@fuchs.com) • [www.fuchs.com/de/en](http://www.fuchs.com/de/en)

