





Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Scania.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN CARGO PRO T SAE 5W-20	Premium Performance, extremely fuel-economy engine oil. Specially developed for MAN and SCANIA Euro VI-d commercial vehicle engines with modern exhaust after treatment systems. Offers good cold starting properties and lower oil consumption.	–	SCANIA LDF-5	–
TITAN CARGO FLEX LD SAE 5W-30	Premium Performance, extreme fuel-economy engine oil, specially developed for commercial vehicles with modern exhaust after treatment systems and turbocharger. Offers good cold starting and lower oil consumption.	ACEA E11, E8, E7 API CK-4/SN	SCANIA LDF-4	–
TITAN CARGO LD3 EVO SAE 10W-40	Premium Performance, fuel-economy engine oil for use in Scania Euro VI vehicles. Specially developed for extended service intervals.	ACEA E7, E4	SCANIA LDF-3	API CF SCANIA LDF-2
Gear Oils				
TITAN CYTRAC TD SAE 75W-90	Premium Performance Gear Oil for highly-stressed manual transmissions and hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals.	API GL-4/GL-5 API MT-1 SAE J2360	SCANIA STO 1:0 SCANIA STO 1:1 G SCANIA STO 2:0 A FS	–
TITAN CYTRAC PRO GA2 SAE 75W-90	Premium Performance Transmission Oil for manual transmissions in commercial vehicles, especially for SCANIA. Developed for the longest oil change intervals.	API GL-5 SCANIA STO 1:1 G	SCANIA STO 2:0 G	–
TITAN CYTRAC PRO S2A SAE 75W-140	Premium Performance Gear Oil especially for axle- and differential transmissions in Scania commercial vehicles. Developed for longest oil drain intervals.	API GL-5 SCANIA STO 1:0	SCANIA STO 2:0 A	–
TITAN CATRAC PRO S1G SAE 80W-90	Premium Performance Gear Oil especially for axle- and differential transmissions in Scania commercial vehicles.	API GL-4/GL-5 SCANIA STO 1:0	SCANIA STO 1:1 G	–
TITAN SUPERGEAR PRO S1 SAE 80W-140	Ultra High Performance Gear Oil especially for axle- and manual transmissions in SCANIA commercial vehicles.	API GL-5	SCANIA STO 1:0	–
Automatic Transmission Fluids (ATF)				
TITAN ATF 5668	Premium Performance ATF especially developed for highly stressed ALLISON step automatic transmissions in commercial vehicles. Product dyeing: red.		ALLISON TES 668®	ALLISON TES 295 ALLISON TES 389
TITAN ATF 5500	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: none.	–	ZF TE-ML 04D, 14C, 16M, 16S, 20C, 25C (ZF001797)	DEXRON III (H) ALLISON TES 295 ALLISON TES 389 VOITH H55.6336.xx
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	–	ALLISON C-4 ALLISON TES 389 DEXRON III (H)

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Antifreeze				
FRICOFIN DP 	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines and phosphates with Si-OAT-technology. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: pink-violet.	ASTM D 3306 TYPE I ASTM D 4985	–	SCANIA TB 1451
Brake Fluids				
TITAN DOT 514 LV 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 08/2024

FUCHS LUBRICANTS GERMANY GmbH
 Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
 Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
 E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

PARTNER
 des deutschen Kraftfahrzeuggewerbes

