

TITAN

Engine Oils for Passenger Cars



LUBRICANTS.
TECHNOLOGY.
PEOPLE.



MOVING YOUR WORLD

TITAN PRO- and TITAN FLEX-Series

PRO STANDS FOR PROFESSIONAL

This range is characterized by its strong focus on a single, specific OEM specification. Therefore, this oil has been specially developed, optimized and released for these requirements.

FLEX STANDS FOR FLEXIBLE

TITAN FLEX products combine a large number of approvals in order to achieve the broadest possible market coverage. The oils are developed according to the respective ACEA sequence. The engine oil with the largest market coverage is our TITAN GT1 FLEX C23 SAE 5W-30.

Professional use

OEM approval: STELLANTIS
FPW9.55535/03, for many
Peugeot, Citroën and Opel
engines

TITAN GT1 PRO FPW03 SAE 5W-30

TITAN GT1 FLEX C23 SAE 5W-30

Flexible applications

ACEA sequence:
C2 und C3

TITAN

GT1 PRO GLV-1

SAE 0W-8

Premium performance engine oil, ultra low viscosity. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers such as TOYOTA.

- extreme fuel-economy characteristics and reduced CO₂ emissions
- excellent cold starting behaviour
- very fast oil circulation
- outstanding performance reserves



Specifications:

JASO GLV-1

Approvals:

—

FUCHS Recommendations:

—

TITAN

GT1 FLEX 5

SAE 0W-20

Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers.

- extreme fuel-economy characteristics and reduced CO₂ emissions
- excellent cold starting behaviour
- very fast oil circulation
- outstanding performance reserves



Specifications:

ACEA C6, C5, API SN PLUS RC
API SP RC, ILSAC GF-6A
FORD WSS-M2C954-A1

Approvals:

BMW LONGLIFE-17 FE+
JAGUAR LAND ROVER STJLR.03.5006
MB-APPROVAL 229.71/72
OPEL OV0401547 – A20

FUCHS Recommendations:

CHRYSLER MS-12145
FIAT 9.55535-GSX
FORD WSS-M2C947-A/B1
FORD WSS-M2C962-A1, ILSAC GF-5
JAGUAR LAND ROVER, STJLR.51.5122
VOLVO VCC RBS0-2AE, VWC 53057

TITAN

GT1 FLEX 952

SAE 0W-20

Premium Performance Engine Oil specially designed for modern FORD vehicles. Additionally applicable in hybrid vehicles of different manufacturers.

- extreme fuel-economy characteristics and reduced CO₂ emissions
- excellent cold starting behaviour
- very fast oil circulation
- outstanding performance reserves



Specifications:

ACEA C6, C5; API SN PLUS; API SP
FORD WSS-M2C952-A1

Approvals:

JAGUAR LAND ROVER STJLR.03.5006
MB-APPROVAL 229.71
OPEL OV0401547 – A20

FUCHS Recommendations:

FORD WSS-M2C947-A
FORD WSS-M2C947-B1
FORD WSS-M2C962-A1
ILSAC GF-5

TITAN

GT1 LONGLIFE IV

SAE 0W-20

Premium Performance Engine Oil in ground-breaking viscosity class. Specially designed for modern VW vehicles incl. hybrid models.

- extreme fuel-economy characteristics and reduced CO₂ emissions
- excellent cold start properties
- very fast oil circulation
- outstanding performance reserves



Specifications:

ACEA C5
FORD WSS-M2C956-A1

Approvals:

PORSCHE C20
VW 508 00/509 00

FUCHS Recommendations:

—

TITAN

GT1 FLEX C2

SAE 0W-30

Premium Performance engine oil for modern cars and vans. Especially developed for BMW and Mercedes-Benz vehicles with exhaust gas aftertreatment and turbochargers. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers.

- excellent cold start properties
- low oil consumption
- reduced emissions



Specifications:
ACEA C2, ACEA A5/B5
API SP, API SP RC
ILSAC GF-6A
FORD WSS-M2C950-A

Approvals:
BMW LONGLIFE-12 FE
DTFR 15D100
MB-APPROVAL 229.61

FUCHS Recommendations:
FIAT 9.55535-GS1
JAGUAR LAND ROVER
STJLR.03.5007
MB 227.61, VWC 53035

TITAN

GT1 FLEX C3

SAE 0W-30

Premium Performance engine oil for modern cars and vans. Especially developed for BMW, VW, Porsche und Mercedes-Benz vehicles with exhaust gas aftertreatment and turbochargers. Additionally applicable in hybrid vehicles of different manufacturers such as BMW, Mercedes-Benz or VW.

- excellent cold start properties
- low oil consumption
- reduced emissions



Specifications:
ACEA C3
Approvals:
BMW LONGLIFE-04
MB-APPROVAL 229.31
MB-APPROVAL 229.51
MB-APPROVAL 229.52
PORSCHE C30
VW 504 00/507 00

FUCHS Recommendations:
API SN
CHRYSLER MS-11106
FIAT 9.55535-S3

TITAN

GT1 PRO 2312

SAE 0W-30

Premium Performance, fuel-economy engine oil for modern passenger cars and light commercial vehicles. Specially developed for latest PSA gasoline and diesel vehicles with exhaust after treatment and turbocharger.

- excellent cold start properties
- lower oil consumption
- minimized exhaust emissions



Specifications:
ACEA C2
Approvals:
PSA B71 2312

FUCHS Recommendations:
CHRYSLER MS-13340
CHRYSLER MS.90047
FIAT 9.55535-DS1/GS1
IVECO 18-1811 CLASSE SC1 LV
IVECO 18-1811 CLASSE SC1 LV-16

TITAN

GT1 FLEX C23

SAE 5W-30

Premium Performance, extreme fuel-economy engine oil. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers such as Audi or Mercedes-Benz.

- optimum cold start ability
- outstanding performance reserves for modern passenger cars and light commercial vehicles with or without extended service intervals



Specifications:
ACEA C3, C2
API SQ
Approvals:
BMW LONGLIFE-04
MB-APPROVAL 229.51
MB-APPROVAL 229.52
OPEL OV0401547 – D30
OPEL OV0401547 – G30

FUCHS Recommendations:
CHRYSLER MS-11106
FIAT 9.55535-S1 / -S3
GM-LL-A-025, GM-LL-B-025
IVECO 18-1811 CLASSE SC1
MB 229.31, VW 505 00/505 01

TITAN

GT1 PRO C-3

SAE 5W-30

Premium Performance, extreme fuel-economy engine oil. Specially developed for BMW, VW and Mercedes-Benz vehicles with exhaust after treatment and turbo-charger and also applicable for their hybrid vehicles.

- optimum cold start ability
- outstanding performance reserves for modern passenger cars and light commercial vehicles with or without extended service intervals



Specifications:

ACEA C3
API SN

Approvals:

BMW LONGLIFE-04
MB-APPROVAL 229.51
PORSCHE C30
VW 504 00/507 00

FUCHS Recommendations:

CHRYSLER MS-11106
FIAT 9.55535-S3
MB 229.52
RENAULT RN0700/0710

TITAN

GT1 PRO FPW03

SAE 5W-30

Premium Performance engine oil for passenger cars and light commercial vehicles, specially developed for Stellantis engines requiring the new specification FPW9.55535/03.

- optimum cold starting
- reduced oil consumption
- minimised exhaust emissions



Specifications:

ACEA C3
API SQ

Approvals:

–

FUCHS Recommendations:

OPEL OV0401547 – D30
OPEL OV0401547 – G30
PSA B71 2290
PSA B71 2297
STELLANTIS FPW9.55535/03

TITAN

GT1 FLEX DE

SAE 5W-30

Premium Performance, extreme fuel-economy engine oil. With BlueEV Technology additionally applicable in hybrid vehicles of different manufacturers such as Audi or Mercedes-Benz.

- optimum cold start ability
- outstanding performance reserves for modern passenger cars and light commercial vehicles with or without extended service intervals



Specifications:

ACEA C3
API SP

Approvals:

BMW LONGLIFE-04
MB-APPROVAL 229.51
MB-APPROVAL 229.52
OPEL OV0401547 – D30
OPEL OV0401547 – G30
PORSCHE C30
VW 504 00/507 00

FUCHS Recommendations:

–

TITAN

GT1 FLEX FR

SAE 5W-30

Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for PSA and Renault vehicles with exhaust after treatment and turbo-charger. Additionally applicable in hybrid vehicles of different manufacturers.

- optimum cold starting
- lower oil consumption
- minimized exhaust emissions



Specifications:

ACEA C3, C2
API SP

Approvals:

MB-APPROVAL 226.52
MB-APPROVAL 229.51
MB-APPROVAL 229.52
PSA B71 2290
RENAULT RN17

FUCHS Recommendations:

FIAT 9.55535-S1
RENAULT RN0700/0710
MB 229.31

BluEV
TECHNOLOGY

Always one step ahead. With BluEV Technology.

As a pioneer for the mobility of the future, we have developed over 10,000 lubricants for more than 90 years. With the brand TITAN, FUCHS has been represented in many electric and hybrid vehicles from leading premium manufacturers for a long time.

BluEV Technology stands for:

- many years of experience and solid automotive know-how,
- performance, reliability and efficiency,
- advanced lubricant solutions.



BluEV Technology builds the bridge between existing and new products and their application in conventional vehicles with combustion engines as well as hybrid and electric vehicles.

We therefore offer a comprehensive range of lubricants for all automotive applications, including electric powertrains. So we can take the step into the mobility of the future together.



TITAN

GT1 FLEX 34

SAE 5W-30

Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially for Renault and Mercedes-Benz engines with exhaust after treatment and turbocharger.

- optimum cold start properties
- lower oil consumption
- minimized exhaust emissions



Specifications:

ACEA C4, C3

Approvals:

MB-APPROVAL 226.51

MB-APPROVAL 229.51

RENAULT RN0720

FUCHS Recommendations:

FIAT 9.55535-S4

TITAN

GT1 PRO C-1

SAE 5W-30

Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals.

- specially developed for vehicles with exhaust after treatment and turbocharger
- optimum cold start properties
- lower oil consumption
- minimized exhaust emissions



Specifications:

—

Approvals:

JAGUAR LAND ROVER

STJLR.03.5005

FUCHS Recommendations:

ACEA C1

JASO DL-1

FORD WSS-M2C934-B

TITAN

GT1 FLEX 3

SAE 5W-40

Premium Performance engine oil. For modern passenger cars and light commercial vehicles with or without extended oil drain intervals. Especially developed for vehicles with exhaust aftertreatment and turbocharger.

- optimum cold starting
- reduced oil consumption
- minimised exhaust emissions



Specifications:

ACEA C3

API SN

Approvals:

BMW LONGLIFE-04

MB-APPROVAL 229.31/51/52

PORSCHE C40

RENAULT RN0700/RN0710

VW 511 00

FUCHS Recommendations:

API CF, CHRYSLER MS-10725

FIAT 9.55535-GH2/-S2/-T2

FORD WSS-M2C917-A, MB 226.5

VW 505 00/505 01

TITAN

SUPERSYN FE

SAE 0W-30

Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals.

- excellent cold starting properties
- low oil consumption



Specifications:

ACEA A5/B5

API SL

Approvals:

VOLVO VCC 95200377

FUCHS Recommendations:

RENAULT RN0700

TITAN SUPERSYN LONGLIFE PLUS SAE 0W-30

Ultra High Performance, extreme fuel-economy engine oil formulated with fully synthetic base oil for VW engines. Specially developed for VW Longlife Technology.

- for all passenger car gasoline and diesel engines with or without pump injector technology
- excellent cold start properties
- lower oil consumption



Specifications:

–

Approvals:
VW 506 01

FUCHS Recommendations:
VW 503 00/506 00

TITAN SUPERSYN LONGLIFE SAE 0W-30

Ultra High Performance, extreme fuel-economy engine oil for a variety of vehicles with or without extended service intervals.

- excellent cold start properties
- lower oil consumption



Specifications:

ACEA A3/B4
API SL

Approvals:

–

FUCHS Recommendations:
MB 229.5
VW 502 00/505 00

TITAN SUPERSYN LONGLIFE SAE 0W-40

Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals.

- excellent cold start properties
- lower oil consumption



Specifications:

ACEA A3/B4
API SP
API SN

Approvals:
MB-APPROVAL 229.5
VW 502 00/505 00

FUCHS Recommendations:
BMW LONGLIFE-01
FORD WSS-M2C937-A
MB 229.3
MB 226.5
RENAULT RN0700/RN0710

TITAN SUPERSYN LONGLIFE SAE 5W-40

Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals.

- optimum cold starting
- lower oil consumption



Specifications:

ACEA A3/B4
API SP

Approvals:
BMW LONGLIFE-01
MB-APPROVAL 229.5
PORSCHE A40
PSA B71 2296
RENAULT RN0700/RN0710
VW 502 00/505 00

FUCHS Recommendations:
CHRYSLER MS-12991
FIAT 9.55535-H2/M2/N2/Z2
MB 226.5

TITAN SUPERSYN F ECO-B SAE 5W-20

Ultra High Performance, extreme fuel-economy engine oil especially developed for Ford EcoBoost gasoline engines.

- optimum cold start properties
- lower oil consumption

TITAN SUPERSYN F ECO-DT SAE 5W-30

Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines.

- optimum cold starting
- lower oil consumption



Specifications:

ACEA C5
API SN
FORD WSS-M2C948-B

Approvals:

JAGUAR LAND ROVER
STJLR.03.5004

FUCHS Recommendations:

ACEA A1/B1
CHRYSLER MS 6395
FIAT 9.55535-CR1
FORD WSS-M2C925-A/B
FORD WSS-M2C945-A
ILSAC GF-5

Specifications:

ACEA A5/B5
API SL
FORD WSS-M2C913-D

Approvals:

JAGUAR LAND ROVER STJLR.03.5003

FUCHS Recommendations:

ACEA A1/B1, API CF
CHRYSLER MS 6395
FORD WSS-M2C913-A/B/C
IVECO 18-1811 CLASSE S1/S2
JAGUAR M2C913-B
RENAULT RN0700
VWC 53036

TITAN SUPERSYN D1 SAE 0W-20

Ultra High Performance, extreme fuel-economy engine oil, specially developed for GM gasoline engines requiring dexos1™ Gen 3 fluid.

- optimum cold start properties
- lower oil consumption
- minimized exhaust emissions



Specifications:

API SN PLUS RC
API SP RC
ILSAC GF-6A

Approvals:

dexos1™ Gen 3 (D335BDDH075)

FUCHS Recommendations:

CHRYSLER MS 6395
CHRYSLER MS-12145
FIAT 9.55535-CR1/-GSX
FORD WSS-M2C947-A/B1
FORD WSS-M2C962-A1
ILSAC GF-5

TITAN SUPERSYN D1 SAE 5W-30

Ultra High Performance, extreme fuel-economy engine oil, specially developed for gasoline engines requiring dexos1™ Gen 3 fluid.

- optimum cold start properties
- lower oil consumption
- minimized exhaust emissions



Specifications:

API SN PLUS RC
API SP RC
ILSAC GF-6A

Approvals:

dexos1™ Gen 3 (D335ABDF075)

FUCHS Recommendations:

FORD WSS-M2C929-A
FORD WSS-M2C946-A/B1
FORD WSS-M2C961-A1
FIAT 9.55535-CR1
CHRYSLER MS 6395
GM 6094M/4718M
ILSAC GF-5

TITAN SUPERSYN SAE 5W-40

Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals.

- optimum cold start properties
- lower oil consumption

TITAN SUPERSYN SAE 5W-50

Ultra High Performance, fuel-economy engine oil for passenger cars.

- optimum cold start properties
- low oil consumption
- highly durable lubricating film
- high oil pressure



Specifications:

ACEA A3/B4
API SN/SM

Approvals:

MB-APPROVAL 229.3
RENAULT RN0700/RN0710
VW 502 00/505 00

FUCHS Recommendations:

API CF
BMW LONGLIFE-98
CHRYSLER MS-12991
FIAT 9.55535-H2/M2/N2/Z2
GM-LL-A-025/B-025



Specifications:

—

Approvals:

—

FUCHS Recommendations:

ACEA A3/B4
API SL/CF

TITAN SUPERSYN SAE 10W-60

Ultra High Performance, fuel-economy engine oil for passenger cars.

- lower oil consumption
- highly durable lubricating film
- high oil pressure



Specifications:

—

Approvals:

—

FUCHS Recommendations:

ACEA A3/B3
API SL/CF
FIAT 9.55535-H3

TITAN SYN MC SAE 10W-40

Super High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars.

- lower oil consumption



Specifications:

ACEA A3/B4
API SN

Approvals:

MB-APPROVAL 229.3
RENAULT RN0700/RN0710
VW 501 01/505 00

FUCHS Recommendations:

API CF
FIAT 9.55535-D2/G2
MB 229.1
PSA B71 2300

Note

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH.

© FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 12/2025

Contact:

FUCHS LUBRICANTS GERMANY GmbH

Friesenheimer Straße 19
68169 Mannheim/Germany
Phone: +49 621 3701-0
Fax: +49 621 3701-7000
E-mail: zentrale-flg@fuchs.com
www.fuchs.com/de/en

Export Division

Friesenheimer Straße 19
68169 Mannheim/Germany
Phone: +49 621 3701-1703
Fax: +49 621 3701-7719
E-mail: export-flg@fuchs.com
www.fuchs.com/de/en