















Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Toyota.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN GT1 PRO GLV-1 SAE 0W-8 	Premium performance engine oil, ultra low viscosity, specially designed for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers such as TOYOTA.	JASO GLV-1	–	–
TITAN GT1 FLEX 5 SAE 0W-20 	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. Additionally applicable in hybrid vehicles of different manufacturers such as Toyota.	ACEA C6, C5 API SN PLUS RC API SP RC ILSAC GF-6A	–	ILSAC GF-5
TITAN GT1 PRO 2312 SAE 0W-30	Premium Performance, fuel-economy engine oil for modern passenger cars and light commercial vehicles. Specially developed for latest PSA gasoline and diesel vehicles with exhaust after treatment and turbocharger. Excellent cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C2	–	–
TITAN GT1 FLEX C23 SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C3, C2 API SQ	–	–
TITAN SYN SP SAE 0W-16 	Ultra High Performance low viscosity engine oil for a variety of petrol engines in passenger cars.	API SP RC ILSAC GF-6A	–	–
TITAN SUPERSYN F ECO-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A5/B5 API SL	–	API CF
TITAN SUPERSYN SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM	–	API CF
Gear Oils				
TITAN SINTOFLUID FE SAE 75W 	Premium Performance Manual Transmission Fluid offering increased efficiency in passenger cars due to its low viscosity and can also be used in reducer gearboxes of hybrid vehicles. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–

Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 inkl. LS	–	–
Automatic Transmission Fluids (ATF)				
TITAN ATF 8400 ULV  Advanced Circular Technologies	Premium Performance ATF with extremely reduced viscosity specifically formulated for automatic transmissions of Japanese manufacturers. Product dyeing: red.	–	–	AISIN WARNER AW-2 DEXRON ULV
TITAN ATF 6400 	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.	–	DEXRON VI	AISIN WARNER/ AW-1 JWS 3324 TOYOTA TYPE WS
TITAN ATF 4400 	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	–	–	DEXRON III JWS 3309/TYP T-IV TOYOTA TYPE D-2/T/T-II/T-III/T-IV
Continuously Variable Transmission Fluids (CVTF)				
TITAN CVTF FLEX 	Premium Performance CVTF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	TOYOTA TC/CVT FE
Antifreeze				
FRICOFIN PS 	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites and borates with Psi-OAT-technology. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: green.	ASTM D3306-20 TYPE I ASTM D4985 BS 6580:2010 JIS K2234:2018	–	Toyota 1WW/2WW
FRICOFIN AV  	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, borates, amines and silicates with P-OAT-technology. Offers frost protection down to -40°C. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: blue.	ASTM D3306-20 ASTM D6210-17 GB 29743-2013 JIS K 2234:1994 JIS K 2234:2006 JIS K 2234:2018 KS M 2142:2014	–	TOYOTA TSK 2601G-8A
FRICOFIN LD	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF	–	–
Brake Fluids				

LUBRICANTS FOR TOYOTA PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN DOT 514 LV 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	–
Greases				
Renolit LX-PEP 2	Multipurpose grease, wheel bearings of motor vehicles, roller bearings of e-motors, needle bearings of cardan shafts, plain and roller bearings, ventilator grease.	KP 2 N-30 ISO-L- XC(F)DEB 2	MB Freigabe 265.1, ZF TE-ML 12, Schaeffler Gruppe, VW TL 52 147 X, Interprecise (IDC-Bearings), Deutsche Bahn	–
Renolit JP 1619	EP-grease with additive for improve corrosion protection, ageing resistance and adhesiveness, lubrication of friction points requiring very good sliding behaviour, low start-up resistance, also at low temperature, e.g. rack and pinion steerings, prop shafts, high-speed bearings	–	Dana Spicer Bosch	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 01/2026

FUCHS LUBRICANTS GERMANY GmbH
 Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
 Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
 E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

