



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Volvo.

| Product name | Description | Specifications | Approvals | FUCHS Recommendations |
|---|---|--|---|---|
| Engine Oils | | | | |
| TITAN CARGO MAXX II SAE 5W-30 | Premium MAXX Performance Engine Oil. Especially developed for vehicles with exhaust aftertreatment and turbocharger. Optimum cold start properties and ageing stability for a very good fuel economy throughout the drain interval. | ACEA E11, E8, E7, E4 API CK-4/CJ-4 | VOLVO VDS-4.5 | ACEA E9, E6 |
| TITAN CARGO MAXX II SAE 10W-40 | Premium MAXX Performance Engine Oil. Especially developed for vehicles with exhaust aftertreatment and turbocharger. Good cold start properties and excellent ageing stability for fuel economy throughout the drain interval. | ACEA E11, E8, E7, E4 API CK-4/CJ-4 | VOLVO VDS-4.5 | ACEA E9, E6 VOITH-RETARDER „B“ |
| TITAN CARGO FLEX A-4 SAE 5W-30 | Premium Performance, extreme fuel-economy engine oil. Specially developed for commercial vehicles with modern exhaust after treatment systems. Suitable for Euro VI engines. Offers good cold starting and lower oil consumption. | API FA-4 | VOLVO VDS-5 MACK EOS-5 RENAULT RLD-5 | CUMMINS CES 20087 DETROIT DIESEL 93K223 FORD WSSM2C214-B1 |
| TITAN CARGO SAE 5W-40 | Premium Performance, fuel-economy engine oil, specially developed for commercial vehicle diesel engines with extended service intervals, exhaust after treatment and turbocharger. | ACEA E11 API CK-4/CJ-4/SN | CUMMINS CES 20086 MACK EOS-4.5 RENAULT RLD-3 VOLVO VDS-4.5 | ACEA E9 DETROIT DIESEL 93K222 RENAULT RLD-4 |
| TITAN TRUCK PLUS SAE 15W-40 | Ultra High Performance engine oil based on the sustainable FUCHS Advanced Circular Technology (ACT) for a variety of diesel and petrol engines. Specially for highly loaded commercial vehicle diesel engines. Low oil consumption. | ACEA E7 API CI-4/SL | VOLVO VDS-3 RENAULT RLD/RLD-2 | – |
| <small>Advanced Circular Technologies</small> | | | | |
| Gear Oils | | | | |
| TITAN CYTRAC TD SAE 75W-90 | Premium Performance Gear Oil for highly-stressed manual transmissions and hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals. | API GL-4/GL-5 API MT-1 SAE J2360 | VOLVO 97312 | – |
| TITAN CYTRAC ULTRA SYNTH SAE 75W-80 | Premium Performance Gear Oil for gear boxes in commercial vehicles, especially developed for ZF heavy duty transmissions with and without Intarder. Reduces fuel consumption by improving gearbox efficiency. Suitable for longest oil change intervals. | API GL-4 VOLVO 97307 | – | VOITH-RETARDER „C“ |
| TITAN CYTRAC MAT SAE 75W-80 | Premium Performance Gear Oil for gear boxes in commercial vehicles, specially developed for manual and automatic ZF-gear boxes, formulated with selected base oils. Reduces fuel consumption by improving gearbox efficiency. Suitable for the longest oil change intervals and compatible with Carbon-Synchronizers. | API GL-4 | – | VOLVO 97305 VOLVO 97307 |
| TITAN SUPERGEAR MC SAE 80W-90 | Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals. | API GL-4/GL-5 | – | VOLVO 97310 |
| TITAN SUPERGEAR MC SAE 80W-140 | Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals. | – | – | API GL-4/GL-5 VOLVO 97310 |

| Product name | Description | Specifications | Approvals | FUCHS Recommendations |
|--|--|--|---------------------------------------|-------------------------------------|
| TITAN GEAR HYP LD SAE 80W-90 | High Performance Gear Oil specially developed for Mercedes-Benz commercial vehicles. Offering enhanced thermal stability and fuel-economy potential. | API GL-5 API MT-1 SAE J2360 | VOLVO 97321 | – |
| Automatic Transmission Fluids (ATF) | | | | |
| TITAN ATF 5668 | Premium Performance ATF especially developed for highly stressed ALLISON step automatic transmissions in commercial vehicles. Product dyeing: red. | – | – | VOLVO 97340 VOLVO 97341 |
| TITAN ATF 5500 | Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: none. | – | VOLVO 97341 VOITH 150.014524.xx | DEXRON III (H) VOITH H55.6336.xx |
| TITAN ATF 4000 | Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Improved low-temperature shifting compared to DEXRON II. Product dyeing: red. | – | VOLVO 97341 VOITH H55.6335.xx | DEXRON III (H) VOLVO 97340 |
| Central Hydraulic / Power Steering Fluids | | | | |
| TITAN CHF 11S | Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green. | – | – | VOLVO 1161529 |
| TITAN CHF 202 BluEV TECHNOLOGY | Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: green. | – | – | VOLVO 30741424 |
| Antifreeze | | | | |
| FRICOFIN LD NEU | Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange. | ASTM D3306 TYPE I ASTM D6210 TYPE I-FF VOLVO VCS-2 | – | – |
| Brake Fluids | | | | |
| TITAN DOT 514 LV BluEV TECHNOLOGY NEU | Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. | FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5- 1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704 | – | – |
| Greases | | | | |
| RENOLIT FLM 2 | For mechanically loaded lubricating points, grease with MoS ₂ , agricultural machines, commercial vehicles, construction industry, quarries and mining, rubber and concrete factory | KPF 2 N-30 ISO-L- XC(F)DEB 2 | – | – |

LUBRICANTS FOR VOLVO COMMERCIAL VEHICLES



| Product name | Description | Specifications | Approvals | FUCHS Recommendations |
|-----------------------------|---|-----------------------------------|-----------|-----------------------|
| RENOLIT LZR 000 | Semi-fluid grease for central lubricating systems of commercial vehicles | GP 00-000 G-40 | – | – |
| RENOLIT LX-PEP 2 | Multipurpose grease, wheel bearings of motor vehicles, roller bearings of e-motors, needle bearings of cardan shafts, plain and roller bearings, ventilator grease. | KP 2 N-30 ISO-L- XC(F)DEB 2 | – | – |
| RENOLIT MP 735 | Multipurpose grease, roller and plain bearings in the chassis area. | KP 2 K-40 ISO-L- XD(F)CEB 2 | – | – |

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 01/2026

FUCHS LUBRICANTS GERMANY GmbH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

