









# LUBRICANTS FOR MG PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for MG.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN GT1 FLEX 5 SAE 0W-20</b>  	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO <sub>2</sub> emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers.	ACEA C6, C5 API SN PLUS RC API SP RC 中国国标 GB 11121 ILSAC GF-6A	–	ILSAC GF-5
<b>TITAN GT1 FLEX C23 SAE 5W-30</b>  	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers such as Audi or Mercedes-Benz.	ACEA C3, C2 API SQ 中国国标 GB 11121	–	–
<b>TITAN SUPERSYN LONGLIFE SAE 0W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting and lower oil consumption.	ACEA A3/B4 API SP API SN 中国国标 GB 11121	–	–
<b>TITAN SYN SP SAE 0W-20</b>	Ultra High Performance low viscosity engine oil for a variety of petrol engines in passenger cars. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers.	API SP RC ILSAC GF-6A 中国国标 GB 11121	–	ILSAC GF-5
<b>TITAN SYN SP SAE 0W-30</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP ILSAC GF-6A 中国国标 GB 11121	–	–
<b>TITAN SYN SP SAE 5W-30</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP ILSAC GF-6A 中国国标 GB 11121	–	–
<b>TITAN SYN SP SAE 5W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP 中国国标 GB 11121	–	ILSAC GF-6A ILSAC GF-5
<b>TITAN SYN SP SAE 10W-30</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP ILSAC GF-6A 中国国标 GB 11121	–	–
<b>TITAN SYN MC SAE 10W-40</b>	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.	ACEA A3/B4 API SN 中国国标 GB 11121	–	API CF
<b>Gear Oils</b>				

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN SINTOFLUID SAE 75W-80</b>	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
<b>TITAN SINTOFLUID SAE 75W-85</b>	Premium Performance fuel-economy passenger car axle fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	–
<b>TITAN SUPERGEAR SAE 80W-90</b>	High Performance Gear Oil for highly-stressed differentials in commercial vehicles and passenger cars.	API GL-4/GL-5	–	–
<b>TITAN GEAR HYP SAE 90</b>	High Performance LS (Limited Slip) hypoid gear oil for axles with or without limited slip differentials.	API GL-5 SAE J306: 85W-90	–	–
<b>TITAN GEAR LS SAE 90</b>	Ultra High Performance Gear Oil for extended oil change intervals.	API GL-5 SAE J306: 85W-90	–	–
<b>Double Clutch Transmission Fluids (DCTF)</b>				
<b>TITAN FFL-2</b> 	Premium Performance DCTF. Specially developed for wet clutch DCTs and hybridized DCTs (DQ400e). Provides optimum wear protection and excellent friction properties even under hard conditions and offers best shifting performance over the whole lifetime. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers such as VW.	–	JAC DTF630 VW TL 52 182 (G 052 182)	–
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TITAN ATF 4400</b> 	Ultra High Performance ATF based on the sustainable FUCHS Advanced Circular Technology (ACT) specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III (H)
<b>TITAN ATF 6400</b> 	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers. Product dyeing: red.	FORD MERCON LV JASO M315 TYPE 1A-LV	DEXRON VI (T62BEZ075)	AISIN WARNER/AW-1 DEXRON HP
<b>Continuously Variable Transmission Fluids (CVTF)</b>				
<b>TITAN CVTF FLEX</b> 	Premium Performance CVTF based on the sustainable FUCHS Advanced Circular Technology (ACT) specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	–
<b>Central Hydraulic / Power Steering Fluids</b>				
<b>TITAN CHF 202</b> 	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: green.	–	–	–
<b>Antifreeze</b>				

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>FRICOFIN LD</b>	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF GB 27943.1-2022	–	–
<b>FRICOFIN LD 50</b>	Premium Performance Coolant Ready-Mix based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Offers frost protection down to -40°C. Product dyeing: orange.	ASTM D3306 TYPE III ASTM D6210 TYPE III-FF GB 27943.1-2022	–	–
<b>Brake Fluids</b>				
<b>TITAN DOT 514 LV</b>  	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K 2233 CLASS 3/4/5/6 SAE J1703/1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GMBH. All Rights reserved. Issue 01/2026

FUCHS LUBRICANTS GERMANY GmbH  
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
E-Mail: [export-flg@fuchs.com](mailto:export-flg@fuchs.com) • [www.fuchs.com/de/en](http://www.fuchs.com/de/en)

**PARTNER**  
des deutschen Kraftfahrzeuggewerbes

