






Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Chery.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN GT1 FLEX 5 SAE 0W-20</b>  	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO <sub>2</sub> emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers.	ACEA C6, C5 API SN PLUS RC API SP RC 中国国标 GB 11121 ILSAC GF-6A	–	ILSAC GF-5
<b>TITAN GT1 LONGLIFE IV SAE 0W-20</b>  	Premium Performance Engine Oil in ground-breaking viscosity class. Specially designed for modern VW vehicles, for extreme fuel-economy characteristics and reduced CO <sub>2</sub> emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers.	ACEA C5	–	中国国标 GB 11121
<b>TITAN GT1 FLEX C23 SAE 5W-30</b>  	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers such as Audi or Mercedes-Benz.	ACEA C3, C2 API SQ 中国国标 GB 11121	–	–
<b>TITAN SUPERSYN LONGLIFE SAE 5W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SP 中国国标 GB 11121	–	–
<b>TITAN SYN SP SAE 5W-30</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP ILSAC GF-6A 中国国标 GB 11121	–	–
<b>TITAN SYN SP SAE 5W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP 中国国标 GB 11121	–	ILSAC GF-6A ILSAC GF-5
<b>TITAN SYN SP SAE 10W-30</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP ILSAC GF-6A 中国国标 GB 11121	–	–
<b>TITAN SYN SP SAE 10W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP 中国国标 GB 11121	–	ILSAC GF-6A ILSAC GF-5
<b>TITAN SYN MC SAE 10W-40</b>	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.	ACEA A3/B4 API SN 中国国标 GB 11121	–	API CF
<b>Gear Oils</b>				

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN SINTOFLUID SAE 75W-80</b>	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
<b>TITAN SINTOFLUID SAE 75W-90</b>	Premium Performance Axle Gear Oil for passenger cars, also for high-offset hypoid drives offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	–
<b>TITAN SUPERGEAR SAE 80W-90</b>	Ultra High Performance Gear Oil for extended oil change intervals.	API GL-4/GL-5	–	–
<b>TITAN GEAR HYP SAE 90</b>	High Performance Gear Oil for highly-stressed differentials in commercial vehicles and passenger cars.	API GL-5 SAE J306: 85W-90	–	–
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TITAN ATF 4400</b> <small>Advanced Circular Technologies</small>	Ultra High Performance ATF based on the sustainable FUCHS Advanced Circular Technology (ACT) specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III (H)
<b>Electric Driveline Fluids (EDF)</b>				
<b>FUCHS BluEV EDF 4101</b> <small>BluEV TECHNOLOGY</small>	Premium Performance Electric Driveline Fluid for E-axes with direct cooled e-motors. Suitable for a large amount of asian car manufacturers. Provides high efficiency potential for increased driving range.	–	–	BYD ATTO 2/ATTO 3/SEAL/SEALION 8/TANG BYD DMi HYBRID SYSTEM CHERY eQ7/V23/V27/X3L Li AUTO i8 XPENG G6/X9/P7/P7+/M03 Only for EDF wet applications
<b>Antifreeze</b>				
<b>FRICOFIN LD</b>	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF GB 27943.1-2022	–	–
<b>FRICOFIN LD 50</b>	Premium Performance Coolant Ready-Mix based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Offers frost protection down to -40°C. Product dyeing: orange.	ASTM D3306 TYPE III ASTM D6210 TYPE III-FF GB 27943.1-2022	–	–
<b>Brake Fluids</b>				

# LUBRICANTS FOR CHERY PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN DOT 514 LV</b>  	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5- 1/6/7 JIS K 2233 CLASS 3/4/5/6 SAE J1703/1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GMBH. All Rights reserved. Issue 01/2026

FUCHS LUBRICANTS GERMANY GmbH  
 Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
 Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
 E-Mail: [export-flg@fuchs.com](mailto:export-flg@fuchs.com) • [www.fuchs.com/de/en](http://www.fuchs.com/de/en)

