





Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for JOHN DEERE.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN CARGO MAXX II SAE 5W-30	Premium MAXX Performance Engine Oil. Especially developed for vehicles with exhaust aftertreatment and turbocharger. Optimum cold start properties and ageing stability for a very good fuel economy throughout the drain interval.	ACEA E11, E8, E7, E4 API CK-4/CJ-4	–	ACEA E9, E6
AGRIFARM MOT X-LA SAE 10W-40	Premium Performance Engine Oil for agricultural vehicles. Universal engine oil for application in modern vehicles with exhaust after treatment as well as in older vehicles. Best engine cleanliness and outstanding wear protection.	ACEA E11, E8, E7, E4 API CK-4/CJ-4/CI-4 PLUS/CI-4	–	ACEA E9, E6
TITAN CARGO MC SAE 10W-40	Premium Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption..	ACEA E7, E4 API CI-4	–	–
AGRIFARM MOT SAE 15W-40 <small>Advanced Circular Technologies</small>	Ultra High Performance Engine Oil based on the sustainable FUCHS Advanced Circular Technology (ACT) for normally aspirated and turbocharged diesel engines in tractors and other machinery which make high demands on service intervals and engine cleanliness.	ACEA E7 API CI-4	–	–
Gear Oils				
AGRIFARM UTTO VT	Premium Performance Multifunctional Oil (UTTO/MFO) for use in transmission and hydraulic systems with integrated wet brakes, clutches and differentials for agricultural and construction machinery.	API GL-4	–	JOHN DEERE JDM J20C JOHN DEERE JDM J27
AGRIFARM UTTO MP	Ultra High Performance Multifunctional Oil (UTTO/MFO) for use in transmission and hydraulic systems with integrated wet brakes, clutches and differentials for agricultural and construction machinery.	API GL-4	–	JOHN DEERE JDM J20C
TITAN UTTO B	High Performance Multifunctional oil for gears, axles and hydraulic systems. Especially suitable for transmissions of construction machinery with wet clutches, as well as excavators and forklift trucks.	–	–	JOHN DEERE JDM J20C
AGRIFARM STOU MC PRO SAE 10W-40 <small>Advanced Circular Technologies</small>	Premium Performance Multifunctional Oil (STOU/MFO) of the latest generation for agricultural vehicles.	–	–	ACEA E7, E5, E4, E3 API GL-3/GL-4/API GL-5 in tractors* JOHN DEERE JDM J20C
AGRIFARM GEAR LS SAE 80W-90	High Performance Gear Oil for axles fitted with limited-slip differentials in agricultural machineries.	API GL-5	–	JOHN DEERE JDM J11F
TITAN SUPERGEAR MC SAE 80W-90	Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5	–	JOHN DEERE JDM J11E

Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN SUPERGEAR MC SAE 80W-140	Ultra High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	–	–	API GL-4/GL-5 API MT-1 JOHN DEERE JDM J11E
Antifreeze				
FRICOFIN DP 	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines and phosphates with Si-OAT-technology. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: pink-violet.	ASTM D 3306 TYPE I ASTM D 4985 BS 6580:2010	–	–
FRICOFIN LD 	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF	–	JOHN DEERE JDM H5

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 07/2025

FUCHS LUBRICANTS GERMANY GmbH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en