






Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Changan.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN GT1 FLEX C23 SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers such as Audi or Mercedes-Benz.	ACEA C3, C2 API SQ 中国国标 GB 11121	–	–
TITAN SUPERSYN LONGLIFE SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SP 中国国标 GB 11121	–	–
TITAN SYN SP SAE 5W-30	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP ILSAC GF-6A 中国国标 GB 11121	–	–
TITAN SYN SP SAE 10W-30	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP ILSAC GF-6A 中国国标 GB 11121	–	–
TITAN SYN SP SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of gasoline engines in passenger cars. Low oil consumption.	API SP 中国国标 GB 11121	–	ILSAC GF-6A ILSAC GF-5
TITAN SYN MC SAE 10W-40	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.	ACEA A3/B4 API SN 中国国标 GB 11121	–	API CF
Gear Oils				
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
TITAN SINTOPOID SAE 75W-90	Premium Performance Axle Gear Oil for passenger cars, also for high-offset hypoid drives offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	–
TITAN SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 incl. LS	–	–
TITAN SUPERGEAR SAE 80W-90	Ultra High Performance Gear Oil for extended oil change intervals.	API GL-4/GL-5	–	–
Automatic Transmission Fluids (ATF)				

Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN ATF 6400 	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers. Product dyeing: red.	FORD MERCON LV JASO M315 TYPE 1A-LV	DEXRON VI (T62BEZ075)	–
TITAN ATF 4400 Advanced Circular Technologies	Ultra High Performance ATF based on the sustainable FUCHS Advanced Circular Technology (ACT) specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III (H)
Continuously Variable Transmission Fluids (CVTF)				
TITAN GEAR HYP SAE 90	High Performance Gear Oil for highly-stressed differentials in commercial vehicles and passenger cars.	API GL-5 SAE J306: 85W-90	–	–
Antifreeze				
FRICOFIN LD	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF GB 27943.1- 2022	–	–
Brake Fluids				
TITAN DOT 514 LV 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5- 1/6/7 JIS K 2233 CLASS 3/4/5/6 SAE J1703/1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GMBH. All Rights reserved. Issue 01/2026

FUCHS LUBRICANTS GERMANY GmbH
 Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
 Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
 E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

PARTNER
 des deutschen Kraftfahrzeuggewerbes

