



It's. Your. Car.

Contact:



FUCHS LUBRICANTS CO.
17050 Lathrop Ave.
Harvey, IL 60426
United States
Phone + 1 708-333-8900
E-mail inquiry@fuchs.com
www.fuchs.com/us



The Original Oil.

FUCHS supplies to and develops hand in hand with the major German automotive manufacturers. Our innovative power, development competence and product quality are award winning.

TECHNOLOGY THAT PAYS BACK.

www.fuchs.com/us

VOLKSWAGEN GLOBAL GROUP AWARD
DAIMLER SUPPLIER AWARD
ZF SUPPLIER AWARD





JAGUAR - LAND ROVER	Main Specifications
STJLR 51.5122	Specification for gasoline engines (based on ACEA A1/B1).
STJLR 03.5007	Specification for diesel engines with particulate filter (based on ACEA C2).
STJLR 03.5005	Specification for gasoline and diesel engines with particulate filter (based on ACEA C1)
STJLR 03.5004	Specification for gasoline and diesel engines without particulate filter (based on ACEA A1/B1).
STJLR 03.5003	Specification for gasoline and diesel engines without particulate filter (based on ACEA A5/B5).



SAE OW-20

Premium motor oil with XTL® Technology in path-breaking viscosity class. Specially designed for highly stressed downsized BMW engines with maximum power output, for extreme fuel-economy characteristics and reduced CO₂ emissions. Excellent cold starting behavior, very fast oil circulation and outstanding performance reserves.

 Specifications
 Approvals

 ACEA A1/B1
 JAGUAR LAND ROVER STLJR.51.5122

BMW LONGLIFE-14 FE



TILAN GT1 LL-12 FE

SAE 0W-30

Recommendations

Premium motor oil with XTL® Technology. Specially developed for BMW gasoline and diesel vehicles with exhaust after treatment. Excellent cold starting behavior, lower oil consumption and outstanding performance reserves.

Specifications	Approvals	Recommendations
ACEA C2	BMW LONGLIFE-12 FE	JAGUAR LAND ROVER STJLR 03.5007



IIIAN GT1 PRO C-1

SAE 5W-30

Premium, extreme fuel-economy motor oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after-treatment and turbochargers. Optimum cold-starting behavior, lower oil consumption and minimized exhaust emissions.

Specifications	Approvals	Recommendations
ACEA C1	JAGUAR LAND ROVER STJLR.03.5005	JASO DL-1
		FORD MICC MARCORA D



TILAN Supersyn F ECO-B

SAE 5W-20

Ultra high performance, extreme fuel-economy motor oil specially developed for Ford EcoBoost gasoline engines. Optimum cold-starting behavior and lower oil consumption.

Specifications	Approvals	Recommendations
ACEA A1/B1	JAGUAR LAND ROVER STJLR.03.5004	CHRYSLER MS 6395
ACEA C5		FORD WSS-M2C925-A
API SN		FORD WSS-M2C925-B
FORD WSS-M2C948-B		



TILAN Supersyn F ECO-DT

SAE 5W-30

Ultra high performance, extreme fuel-economy motor oil specially developed for Ford EcoBoost gasoline engines. Optimum cold starting behavior and lower oil consumption.

Specifications	Approvals	Recommendations	
ACEA A1/B1	JAGUAR LAND ROVER STJLR.03.5003	JAGUAR M2C913-B	
ACEA A5/B5		FORD WSS-M2C913-A	
API SL		FORD WSS-M2C913-B	
FORD WSS-M2C913-C / D			



TITAN ATF 6008

Premium performance ATF for passenger car applications. Formulation is specially developed for ZF 8-speed automatc transmissions. Product dyeing: green.

Specifications	Approvals	Recommendations
-	-	JAGUAR 02JDE 26444
		LAND ROVER LR 023288
		ZF S671 090 312

TIM ATF 6006

Premium performance automatic transmission fluid offering maximum performance in passenger car applications. Formulation is specially developed for ZF 6-speed and 5-speed automatic transmissions. Product dyeing: green

Specifications	Approvals	Recommendations
-	-	JAGUAR C2C 8432
		LAND ROVER TYK500050
		ZF S671 090 255

TITAN ATF 6000 SL

Premium performance automatic transmission fluid for passenger car applications such as automatic transmissions with torque converters or wet clutches as well as power steering systems. Formulation is licensed according to DEXRON VI and downwards compatible to any former DEXRON-specification. Product dyeing: red.

Specifications	Approvals	Recommendations
-	DEXRON VI	-

TTAW ATF 4400

Ultra high performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.

Specifications	Approvals	Recommendations
-	-	DEXRON III
		AISIN WARNER/AW-1
		FORD MERCON
		FORD M2C924-A / M2C922-A1
		JWS 3309/TYPE T-IV

TITAN ATF 4000

Ultra high performance automatic transmission fluid. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.

Specifications	Approvals	Recommendations
-	DEXRON III (H)	FORD MERCON

TITAN ATF 1

Ultra high performance ATF for use in automatic transmissions in passenger cars as well as commercial vehicles. Product dyeing: none.

Specifications	Approvals	Recommendations
-	-	JAGUAR JLM 20238
		DEXRON III



SAE 75W-80

Premium performance manual transmission fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill-for-life fluid according to manufacturer.

Specifications	Approvals	Recommendations
API GL-5	-	FORD M2C200-C3

SAE 75W-140

Premium performance multi-functional gear oil, formulated with fully synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.

Specifications	Approvals	Recommendations
API GL-5	-	FORD WSS-M2C200-C/C2





Ultra high performance power steering and central hydraulic oil for automotive applications. Product dyeing: green.

Specifications	Approvals	Recommendations
-	-	LAND ROVER LR003401

MAINTAIN Coolants

SAE J814

MAINTAIN FRICOFIN LL

Premium performance coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange

Specifications	Approvals	Recommendations
JAGUAR LAND ROVER STJLR.651.5003	-	-
FORD WSS-M97-B44-D		
ASTM D 3306 TYPE I		
ASTM D 6210 TYPE I-FF		
BS 6580:2010		