

# LUBRICANTS FOR SCANIA COMMERCIAL VEHICLES



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore SCANIA counts on lubricants and specialties of FUCHS.

Product	Characteristics	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN</b> <b>CARGO MAXX</b> <b>SAE 5W-30</b> 	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Optimum cold starting properties and ageing stability for extreme fuel-economy over the whole drain-interval.	ACEA E9/E7/E6/E4 API CJ-4 SCANIA LA	SCANIA LDF-4	–
<b>TITAN</b> <b>CARGO MAXX</b> <b>SAE 10W-40</b> 	Premium MAXX Performance Engine Oil with new XTL®-Technology. Specially developed for vehicles with modern exhaust after treatment and turbocharger. Good cold starting properties and ageing stability for fuel-economy over the whole drain-interval.	ACEA E9/E7/E6/E4 API CJ-4 JASO DH-2	SCANIA LA	–
<b>TITAN</b> <b>CARGO SL</b> <b>SAE 5W-30</b>	Ultra High Performance, extreme fuel-economy engine oil for a variety of commercial vehicle diesel engines, with optimum cold starting and lower oil consumption. Specially developed for extended service intervals.	ACEA E7/E4	SCANIA LDF-3	–
<b>TITAN</b> <b>CARGO LD3</b> <b>SAE 10W-40</b>	Ultra High Performance, fuel-economy engine oil for use in Scania Euro VI vehicles. Specially developed for extended service intervals.	ACEA E7/E4	SCANIA LDF-3	–
<b>TITAN</b> <b>CARGO MC</b> <b>SAE 10W-40</b>	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of commercial vehicle diesel engines. Specially developed for extended service intervals. Good cold starting and lower oil consumption.	ACEA E7/E4 API CI-4 GLOBAL DHD-1	SCANIA LDF-2	–
<b>Gear Oils</b>				
<b>TITAN</b> <b>CYTRAC TD</b> <b>SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed manual transmissions and hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals.	API GL-4/GL-5 API MT-1 SCANIA STO 1:0 SCANIA STO 2:0A FS	ZF TE-ML 02B	–
<b>TITAN</b> <b>CYTRAC SL</b> <b>SAE 75W-90</b>	Premium Performance Gear Oil for highly-stressed hypoid axles in commercial vehicles formulated with fully-synthetic base oils. Developed for the longest oil change intervals in commercial vehicle axle drives.	API GL-5 SCANIA STO 1:0	–	–
<b>TITAN</b> <b>CYTRAC RR</b> <b>SAE 75W-90</b>	Fully synthetic Premium Performance Hypoid Gear Oil for axle drives in railcars and heavy duty vehicles.	API GL-5 API MT-1 SCANIA STO 1:0	–	–
<b>TITAN</b> <b>SUPERGEAR MC</b> <b>SAE 80W-90</b>	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5 SCANIA STO 1:0	–	–
<b>TITAN</b> <b>SUPERGEAR MC</b> <b>SAE 80W-140</b>	Super High Performance Gear Oil based on MC-Synthesis for extended oil change intervals.	API GL-4/GL-5 SCANIA STO 1:0	–	–
<b>TITAN</b> <b>SUPERGEAR</b> <b>SAE 85W-140</b>	High Performance Gear Oil for extended oil change intervals.	API GL-4/GL-5	–	–

Product	Characteristics	Specifications	Approvals	FUCHS Recommendations
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TTAN</b> ATF 5500	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: none.	–	–	DEXRON III (H) ALLISON TES 295 ALLISON TES 389
<b>TTAN</b> ATF 5005	Premium Performance ATF for automatic transmission in motor vehicles. Outstanding base oil quality for optimal cold temperature properties and high ageing stability. Durable friction properties for excellent wet clutch performance. Product dyeing: red.	–	–	DEXRON III (H) ALLISON TES 295 ALLISON TES 389
<b>TTAN</b> ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	ALLISON C-4 ALLISON TES 389 DEXRON III (H)	–
<b>Antifreeze</b>				
<b>MAINTAIN</b> FRICOFIN DP	Ultra High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: pink - violet.	ASTM D 3306 TYPE I ASTM D 4985 BS 6580:2010 SAE J814	–	SCANIA TB 1451

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Edition 08/2018

## FUCHS SCHMIERSTOFFE GMBH

Export Division ■ Friesenheimer Straße 19 ■ 68169 Mannheim/Germany

Phone: +49 621 3701-1703 ■ Fax: +49 621 3701-7719

E-Mail: [export@fuchs-schmierstoffe.de](mailto:export@fuchs-schmierstoffe.de) ■ [www.fuchs.com/de/en](http://www.fuchs.com/de/en)