

Universal Transmission Fluids

MOVING YOUR WORLD



The TITAN UTTO range is a superior, high performance universal transmission oil designed to meet the latest specifications for off-highway equipment working under the most severe conditions. TITAN UTTO products provide improved wear control, excellent thermal stability, and the elimination of brake 'squawk' in machines fitted with oil immersed brakes.

Designed for use in modern off-highway transmissions, final drives & hydraulics systems, the high performance profiles allows for maximum rationalisation of oils.

Product	Specifications	Approvals	Recommendations
TITAN UTTO PRO 102	API GL-4, SAE J306: 75W-75	VOLVO WB 102	ALLISON C-4, CASE MS 1207 / 1209 / 1210, CATERPILLAR TO-2, FORD M2C86-C / ESN-M2C134-D, JCB 4000/0500 - JCB 4000/2200, JOHN DEERE JDM J20C / J20D, KOMATSU AXO 80 (KES 07.866), KUBOTA UDT FLUID, MASSEY FERGUSON CMS M 1145 / 1143 / 1135, SAE J300: 0W-20, VOLVO WB 101, ZF TE-ML 03E, 05F, 06K, 17E, 21F
TITAN UTTO WB	-	VOLVO WB 101, ZF-TE ML 03E / 03F / 05F / 06K (ZFxxxxxx)	AGCO Q-1826 (Whitefarm), Powerfluid 821 XL, ALLISON C-4, API GL-4, CASE MS 1210 / 1209 / 1207 / 1206 / 1205 / 1204, CATERPILLAR TO-2, CNH MAT 3505 / 3506 / 3525, FNHA-2-C-201.00, FORD ESN M2C41-B / M2C53-B / M2C92-A / M2C134-D, JOHN DEERE JDM J20C / J20D, KUBOTA UDT FLUID, MASSEY FERGUSON CMS M 1145 / 1143 / 1141 / 1135, SAE J300: 10W-30, ZF TE-ML 03L
TITAN UTTO PLUS	SAE J300: 5W-30	-	SAE J306: 75W-80, CASE MS 1207/1209/1210, FORD M2C86-C / ESN-M2C134-D, JOHN DEERE JDM J20C / J20D / J14, KOMATSU KES 07.866, KUBOTA UDT FLUID, MASSEY FERGUSON CMS M 1143 / 1135, STEYR 397.88.0001, VOLVO WB 101
TITAN UTTO ZF	API GL-4	ZF TE-ML 05F / 06K / 17E / 21F (ZF000661)	VOLVO WB 101, ZF TE-ML 03E
TITAN UTTO TO-4 SAE 5W-30	API GL-4, CAT TO-4	-	ALLISON C-4 / TES-439, KOMATSU KES 07.868.1, ZF TE-ML 03C, 07F,
TITAN UTTO TO-4 SAE 10W	API GL-4, CAT TO-4	ZF TE-ML 03C (ZF002186)	ALLISON C-4, KOMATSU KES 07.868.1
TITAN UTTO TO-4 SAE 30	API GL-4, CAT TO-4	ZF TE-ML 03C, 07F (ZF002185)	ALLISON C-4 / TES-439, KOMATSU KES 07.868.1
TITAN UTTO TO-4 SAE 40	API GL-4, CAT TO-4	-	ALLISON C-4 / TES-439, KOMATSU KES 07.868.1
TITAN UTTO TO-4 SAE 50	API GL-4, CAT TO-4	-	KOMATSU KES 07.868.1
TITAN UTTO TO-4 SAE 60	API GL-4, CAT TO-4	-	-

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley,
Stoke on Trent, ST1 5HU
Telephone: +44 (0)1782 203700
E-Mail: contact-uk@fuchs.com
www.fuchs.com/uk

All information correct at time of publication.
Any form of reproduction requires express prior written permission from
FUCHS LUBRICANTS. © FUCHS LUBRICANTS. All rights reserved.