

The complete, cost effective grease system



FUCHS REINER GREASE SYSTEM Dual handle grease gun and cartridge applicator

Makes maintenance simple

The dual handle produces 5800 psi / 400 bar of pressure for improved and easier lubrication of long grease lines.

Large 500g cartridges

REINER cartridges utilise a unique screw fit and are easily removed, resealed and exchanged. Especially suitable for areas that require a greater volume of grease.

Cost effective grease system

There is no need for multiple guns and a flexible hose is also available. A special vacuum principle ensures cartridges are 100% emptied, regardless of whether it is removed from the gun on numerous occasions.

Improved health & safety benefits

The cartridge is in full view, ensuring that the type of grease, recommended applications and safety data are always visible.

100% Efficient

The FUCHS REINER Grease System is designed for long and reliable service. There are no moving parts or outer casing that can be damaged and it has been approved by the German TUV.



FUCHS REINER GREASE GUN

- Dual handle produces 5800 psi / 400 bar of pressure
- Fits large 500g cartridges for high volume greasing
- 100% Emptying of grease cartridges

FUCHS REINER GREASE SYSTEM

Product	Colour	NLGI Grade	Thickener	Temp. Range	Application	Typical Industries
RENOLIT LX-PEP 2	Green	2	Lithium complex	-30°C to 150°C	Ideal for many rotating bearing and sliding applications even under extreme conditions. Extends re-greasing intervals.	Suitable for agriculture, plant/off highway and automotive & CV industries
RENOLIT FLM 2	Black	2	Lithium	-30°C to 140°C	Plain and roller bearings subject to heavy or shock loads	Suitable for the majority of industrial and automotive applications
RENOLIT LX 2	Light brown	2	Lithium complex	-30°C to 160°C	Roller bearings in electric motors, cars, fans & construction machinery	Suitable for all industries, particularly automotive and light industry
RENOLIT MP PLUS	Light brown	2	Lithium	-30°C to 120°C	Cars, trucks and machinery	Suitable for all industries, particularly automotive and light industry



Product and safety data sheets for all grades are available upon request

Greases

Never under-estimate the importance of the right lubricating grease. Greases are an integral part of achieving optimum performance.

FUCHS RENOLIT greases cover a wide variety of applications and specifications to ensure that things run smoothly. The FUCHS REINER Grease System is available with four carefully selected greases.

RENOLIT LX-PEP 2

Heavy duty EP grease with specially selected additives to provide excellent performance characteristics over a wide temperature range. Used in many applications, RENOLIT LX-PEP 2 gives improved load carrying capacity, exceptional anti-corrosion and long life properties even under high thermal and adverse operating conditions.

RENOLIT FLM 2

A premium grease containing molybdenum disulphide to protect against shock loading conditions, as well as additives to improve oxidation resistance, corrosion protection and EP / Anti Wear properties.

RENOLIT LX 2

High performance, water resistant grease, for the long term lubrication of components subject to persistent high temperatures and high loads.

RENOLIT MP PLUS

An excellent multi-purpose EP grease. Offers outstanding corrosion protection, good ageing and wear resistance and excellent low temperature characteristics.

FUCHS LUBRICANTS (UK) plc

New Century Street, Hanley,
Stoke on Trent, ST1 5HU
Telephone: +44 (0)1782 203700
E-Mail: contact-uk@fuchs.com
www.fuchs.com/uk